3 (

n to the

(21) Application No. 53941/74 (22) Filed 13 Dec. 1974

(61) Patent of Addition to No. 1 334 110 dated 16 Feb. 1972

(23) Complete Specification filed 12 Dec. 1975

(44) Complete Specification published 5 Jan. 1978

(51) INT. CL. E02D 29/14

(52) Index at acceptance E1G 96B 96L

(72) Inventor DEREK FERNS



(54) IMPROVEMENTS IN OR RELATING TO INSPECTION COVERS

(71) We, SELFLOCK LIMITED, A British Company of 8 Blaenwern, Avondale Industrial Estate, Cwmbran, Monmouthshire, do hereby declare the invention, for which we pray that a patent may be granted to us, and the method by which it is to be performed, to be particularly described in and by the following statement:—

The invention relates to inspection 10 covers. Such covers include access covers for conduits or the like, manhole covers, access floor panels and covers for providing inspection and access to telephone chambers and similar multiple access pit

15 areas. These covers are usually located in a framework into which they must fit snugly and from which they must be easily removable.

According to the invention there is 20 provided a framework for a manhole or other cavity and a frame for a cover in which one side of the framework and the corresponding side of the frame of the cover are formed of angle sections of identical configuration and with one limb formed to the cover are formed or angle sections.

med to provide an inwardly facing protrusion which extends lengthwise of the section and is bounded on each side by a trough.

The advantages of this design are that the sides of the cover and frame-work may be formed from identical rolled metal stock and a pair of sealing strips may be held in place between the frame and cover.

35 One side of an inspection cover and framework embodying the invention is diagrammatically illustrated, by way of example, in the accompanying drawing.

Referring to the drawing, the inspection 40 cover 1 is substantially rectangular in con-

4, the angle between the two limbs being a right angle.

The upper limb 4 has an inwardly facing protrusion 5 extending substantially along its length and bounded on each side by a 50 trough 6.

The other two opposed sides of the cover are each defined by a flat length or bar of mild steel the depth of the bar being substantially equal to the depth of 55 the angle section.

A framework 10 for receiving the cover 1 is also rectangular in configuration and comprises two opposed sides or boundary walls 12 each made from an angle section 60 of mild steel having a lower limb 13, with a protrusion 15 extending along the length thereof and bounded on each side by a trough 16. The lower limb 13 is integral with an upper limb 14 which is planar, the 65 angle between the limbs being substantially a right angle. The other two sides are, like the cover, defined by flat bars. The framework is set into the concrete walls surrounding the manhole or extending 70 along two sides of an elongate chamber.

The cover includes a reinforcement in the form of a grid 18 of metal bars extending thereacross, and is also filled with concrete, although tiles or other similar 75 building material may be used instead.

It will be appreciated that both angle sections 2 and 12 are identical in configuration, and both are cut from the same length of rolled mild steel stock which is 80 rolled to the required configuration of two limbs subtending approximately a right angle therebetween, one limb having a protrusion along the length thereof.

A pair of sealing strips 17 of flevible oc

SPECIFICATION NO 1496899

By a direction given under Section 17 (1) of the Patents Act 1949 this application proceeded in the name SELF-LEVEL COVERS AKTIENGESELLSCHAFT, a Swiss Body Corporate, of 3 Wallstrasse, Basel, Switzerland.

Bas 451

(11)

(61) Patent of Addition to No. 1 334 110 dated 16 Feb. 1972

(23) Complete Specification filed 12 Dec. 1975

(44) Complete Specification published 5 Jan. 1978

(51) INT. CL.^a E02D 29/14

(52) Index at acceptance E1G 96B 96L

(72) Inventor DEREK FERNS



(54) IMPROVEMENTS IN OR RELATING TO INSPECTION COVERS

(71) We, Selflock Limited, A British Company of 8 Blaenwern, Avondale Industrial Estate, Cwmbran, Monmouthshire, do hereby declare the invention, for which 5 we pray that a patent may be granted to us, and the method by which it is to be performed, to be particularly described in and by the following statement:—

The invention relates to inspection 10 covers. Such covers include access covers for conduits or the like, manhole covers, access floor panels and covers for providing inspection and access to telephone chambers and similar multiple access pit areas. These covers are usually located in a framework into which they must fit snugly and from which they must be easily removable.

According to the invention there is 20 provided a framework for a manhole or other cavity and a frame for a cover in which one side of the framework and the corresponding side of the frame of the cover are formed of angle sections of identical configuration and with one limb formed to provide an inwardly facing protrusion which extends lengthwise of the section and is bounded on each side by a trough.

The advantages of this design are that the sides of the cover and frame-work may be formed from identical rolled metal stock and a pair of sealing strips may be held in place between the frame and cover.

One side of an inspection cover and framework embodying the invention is diagrammatically illustrated, by way of example, in the accompanying drawing.

Referring to the drawing, the inspection 40 cover 1 is substantially rectangular in configuration and comprises two opposed sides or boundary walls 2, of which one is shown in the drawing, each made from an angle section of mild steel having a lower planar limb 3 integral with an upper limb

4, the angle between the two limbs being a night angle.

The upper limb 4 has an inwardly facing protrusion 5 extending substantially along its length and bounded on each side by a 50 trough 6.

The other two opposed sides of the cover are each defined by a flat length or bar of mild steel the depth of the bar being substantially equal to the depth of 55 the angle section.

A framework 10 for receiving the cover 1 is also rectangular in configuration and comprises two opposed sides or boundary walls 12 each made from an angle section of mild steel having a lower limb 13, with a protrusion 15 extending along the length thereof and bounded on each side by a trough 16. The lower limb 13 is integral with an upper limb 14 which is planar, the angle between the limbs being substantially a right angle. The other two sides are, like the cover, defined by flat bars. The framework is set into the concrete walls surrounding the manhole or extending 70 along two sides of an elongate chamber.

The cover includes a reinforcement in the form of a grid 18 of metal bars extending thereacross, and is also filled with concrete, although tiles or other similar 75 building material may be used instead.

It will be appreciated that both angle sections 2 and 12 are identical in configuration, and both are cut from the same length of rolled mild steel stock which is 80 rolled to the required configuration of two limbs subtending approximately a right angle therebetween, one limb having a protrain along the length thereof.

A pair of scaling strips 17 of flexible 85 waterproof material such as Neoprene may be bonded within the troughs 16 bounding the protrusion and provide effective scaling effect.

The angle sections may be formed from 90

materials such as cast iron or moulded synthetic or plastics material, rather than

mild steel as described.

The cover and framework described gives a simple construction as the components are standard, and handling and storage is facilitated since only one angle section member is required for both the framework and cover; stated in another 10 way, the member from which the frame and cover sides 12 and 2 are formed is "reversible" in that it can be used equally for the frame or the cover, being identical in configuration.

WHAT WE CLAIM IS:

1. A framework for a manhole or other cavity and a frame for a cover, in which one side of the framework and the corresponding side of the frame of the cover are 20 formed of angle sections of identical configuration and with one limb formed to provide an inwardly facing protrusion which extends length wise of the section and is bounded on each side by a trough.

2. The combination claimed in claim 1, 25 wherein both angle sections are from the same stock.

3. The combination claimed in claim 1. wherein each trough in the angle section forming part of the framework contains a 30 sealing strip for contact with the angle section forming part of the cover.

4. The combination as claimed in claim 1 substantially as hereinbefore described with reference to and as illustrated in the 35

accompanying drawing.

BROOKES & MARTIN,
Chartered Patent Agents,
High Holborn House, 52/54 High Holborn, London WC1V 6SE. Agents for the applicants.

Printed for Her Majesty's Stationery Office by The Tweeddale Press Ltd., Berwick-upon-Tweed, 1977. Published at the Patent Office, 25 Southampton Buildings, London, WC2A 1AY, from which copies may be obtained.

1496899

COMPLETE SPECIFICATION

1 SHEET

This drawing is a reproduction of the Original on a reduced scale

